


Technical Data Sheet		 <b>Emballage</b>	
<b>STOK - Kunde</b>	Side 1 af 1	Filnavn:	B482325.docx
Ansvar: Kvalitet	Godkendt: JD	Version:	24-02-2020

Item number	103835
Product	LDPE film, 2000 x 0,02 mm
Material	LDPE
Color	Transparent
Density (g/cm <sup>3</sup> )	0.93 ± 5 % g/cm <sup>3</sup> 1 g/min

	Norm	Tolerance
Thicknesses	20 my	±10%
Width	2000 mm	+0-5 %
Length	50 m	+0-5 %

#### Mechanical Properties

	Norm	Method
Tear Strength	MD ≥ 17 N/mm <sup>2</sup>	ISO 527-3
	TD ≥ 17 N/mm <sup>2</sup>	500 mm/min
Elongation at break	MD ≥ 400 %	ISO 527-3
	TD ≥ 400 %	500 mm/min
Coefficient of Friction (μD)	≥ 0,30	DIN 53375

#### Storage:

Recommended storage conditions: temperature 15-25C, RH 40-70%.

Materials should be allowed to reach operating room temperature for 24 hours before use. The Shelf life of this material, if stored in above listed conditions is 12 months from production date.

STOK cannot be held responsible of possible problems caused by expired materials or materials, stored in not recommended conditions.

Date: 24-02-2020

Steffen Øbo

QA Engineer & Lead auditor