

# Product specification

Date:2019-11-01

Index: 2



**Preiss-Daimler  
FibreGlass AB**

## Installation steps



## Product: 6047507 Decomax Färgväv Fiskben (30m) rulle

Description: Standard Glass textile wall covering for indoor walls and ceilings.

Composition: Texturized yarn of glassfiber in warp.  
Sliveryarn of glassfiber in weft.  
Standard soft touch coating

### Technical data:


Properties	Unit	Min value	Nom value	Max value
Width	mm	990	1000	1010
Length deviation	m	-0		
Thickness	mm		0,79	
Total weight	g / m <sup>2</sup>	140	155	170
<b>Tensile strength</b>				
Warp direction	N / 5cm	745	876	
Weft direction	N / 5cm	554	652	

Glue consumption Approx. 250 g / m<sup>2</sup>. See also instructions on the glue bucket.

Paint consumption First coating Second coating  
m<sup>2</sup> / litre 6,4 10,7

### Facing side

Facing side is the outside of the roll.



### Reverse side marking

No marking on this product

### Pattern matching

Offset match - thread to thread.



1,6cm




Pick over warpthread against pick under warpthread

### Allowed amount of marked spot faults

Roll length 15m Max 1  
Roll length 25 & 30m Max 2  
Roll length 50m Max 3

Note: A joint can occur in a roll and is considered as a spot fault.

### Certificates:



Emissionsgeprüfte Wandbekleidung nach ÜNB-Grundsätzen

Storing: -10 to +50 degrees Celcius  
Use within 2 years after production

Information above is accurate to the best of our knowledge. Our products are subject to rigorous quality control along the production line to ensure conformance. Divergence within our tolerance may occur.

Preiss-Daimler Fibreglass AB, Box 7013, S-250 07 Helsingborg. Tel +46 42 25 05 00, Fax + 46 42 16 01 42