

# Product specification

Date:2019-11-01

Index: 2



**Preiss-Daimler  
FibreGlass AB**

## Installation steps



## Product: 6047509 Decomax Färgväv Lågstr Förgr. (50 m) rulle

Description: Precoated Glass textile wall covering for indoor walls and ceilings.

Composition: Texturized yarn of glassfiber in warp.  
Sliveryarn of glassfiber in weft.  
Precoated soft touch coating

### Technical data:


Properties	Unit	Min value	Nom value	Max value
Width	mm	990	1000	1010
Length deviation	m	-0		
Thickness	mm		0,55	
Total weight	g / m <sup>2</sup>	144	160	176
<b>Tensile strength</b>				
Warp direction	N / 5cm	580	680	
Weft direction	N / 5cm	380	445	

Glue consumption Approx. 250 g / m<sup>2</sup>. See also instructions on the glue bucket.

Paint consumption First coating Second coating  
m<sup>2</sup> / litre 7,4

### Facing side

Facing side is the INSIDE of the roll.




### Reverse side marking

No marking on this product

### Pattern matching

Straight match - thread to thread.





Pick over warpthread against pick under warpthread

### Allowed amount of marked spot faults

Roll length 15m Max 1  
Roll length 25 & 30m Max 2  
Roll length 50m Max 3

Note: A joint can occur in a roll and is considered as a spot fault.

### Certificates:



Storing: -10 to +50 degrees Celcius  
Use within 2 years after production

Information above is accurate to the best of our knowledge. Our products are subject to rigorous quality control along the production line to ensure conformance. Divergence within our tolerance may occur.

Preiss-Daimler Fibreglass AB, Box 7013, S-250 07 Helsingborg. Tel +46 42 25 05 00, Fax + 46 42 16 01 42