

# Product specification

Date:2019-11-01

Index: 2



**Preiss-Daimler  
FibreGlass AB**

## **Product: 6075894 Decomax Färgväv Våtrum Fin (25m) rulle**

Description: Glass textile wall covering for wetroom areas

**Note! The product is a part of a system with filler, glue and paint**

Composition: Yarn of glassfiber in warp.

Sliveryarn of glassfiber in weft.

Wetroom coating

### **Technical data:**


Properties	Unit	Min value	Nom value	Max value
<i>Width</i>	mm	990	1000	1010
<i>Length deviation</i>	m	-0		
<i>Thickness</i>	mm		0,37	
<i>Total weight</i>	g / m <sup>2</sup>	108	120	132
<u>Tensile strength</u>				
<i>Warp direction</i>	N / 5cm	340	400	
<i>Weft direction</i>	N / 5cm	425	500	

Glue consumption See instructions on the glue bucket

Paint consumption See instructions on the paint bucket  
*m<sup>2</sup> / litre*

#### **Facing side**

Facing side is the outside of the roll.




#### **Front side marking**

No marking on this product

#### **Pattern matching**

Straight match - thread to thread.



Pick over warpthread against pick under warpthread

#### Allowed amount of marked spot faults

<i>Roll length 15m</i>	Max 1
<i>Roll length 25 &amp; 30m</i>	Max 2
<i>Roll length 50m</i>	Max 3

Note: A joint can occur in a roll and is considered as a spot fault.

#### **Certificates:**

Reaction to fire classification  
Euroclass B-s1,d0

Storing: -10 to +50 degrees Celcius  
Use within 2 years after production

