

tesa® Masking Sensitive 56260 / 56261 (EPI / EEU)

tesa® Masking Tape sensitive has been developed to protect sensitive surfaces like wallpaper or stucco when doing painting jobs like painting the doorframe etc.

The special soft adhesive is finely balanced to provide both safe hold and best removability without damaging the surface. This tape features an extra thin paper contour liner that is especially designed to achieve precise edges between painted areas and expensive wallpapers. This sensitive masking tape features a solvent-free adhesive coating that securely sticks on any flat surface and allows non-destructive and residue-free removal within a period of 7 days.

Main Application

- Protection of smooth and delicate surfaces during indoor painting
- Suitable for applications above 5°C and below 35° C

Technical Data & Properties

Dimensions	25m : 25mm / 25m: 38mm
Backing material	Thin paper backing
Total thickness	85 µm
Type of adhesive	natural rubber
Adhesion to steel	0.6 N/cm (+/- 0.2)
Elongation at break	4,5%
Tensile strength	61 N/cm
UV-resistance	7 days
Hand tearability	●●●●
Suitable for rough surfaces	●
Paint anchorage	●●
Sharp colour edge	●●●
Conformability	●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For the latest information on this product please visit <http://www.tesa.com/consumer>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.